



# SAFETY DATA SHEET

Issuing Date: 10-Jun-2021

Revision Date: 14-Jun-2021

Print Date: 14-Jun-2021

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Name: E4E-100 ROADRUNNER PART A

professional users

## 2. HAZARDS IDENTIFICATION

### Classification

#### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin Corrosion/Irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Flammable Liquids	Category 2

### Label Elements

#### Emergency Overview

**DANGER**

#### Hazard Statements

Harmful if swallowed  
 harmful if inhaled  
 Causes skin irritation  
 Causes serious eye irritation  
 May cause an allergic skin reaction  
 May cause cancer  
 Highly flammable liquid and vapor



**Appearance** Opaque

**Physical state** Liquid

**Odor** Solvent

#### Precautionary Statements - Prevention

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Contaminated work clothing should not be allowed out of the workplace  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/Bond container and receiving equipment  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wear protective gloves/protective clothing/eye protection/face protection

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
 Rinse mouth  
 In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool  
 Store in accordance with local regulations

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

- Toxic to aquatic life with long lasting effects
- Toxic to aquatic life

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Contains a known or suspected carcinogen**

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
METHYL AMYL KETONE	110-43-0	10% - 20%	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
BARIUM SULFATE	7727-43-7	10% - 20%	TWA: 5 mg/m <sup>3</sup> inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction
STRONTIUM CHROMATE	7789-06-2	10% - 20%	STEL: 0.0005 mg/m <sup>3</sup> Cr(VI) inhalable particulate matter TWA: 0.0002 mg/m <sup>3</sup> Cr(VI) inhalable particulate matter S*	TWA: 5 µg/m <sup>3</sup> Ceiling: 0.1 mg/m <sup>3</sup> CrO <sub>3</sub> applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect
NATURAL WOLLASTONITE	13983-17-0	5% - 10%	TWA: 1 mg/m <sup>3</sup> inhalable particulate matter,	N/A

			particulate matter containing no asbestos and <1% crystalline silica	
ACETONE	67-64-1	5% - 10%	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>
TITANIUM DIOXIDE	13463-67-7	5% - 10%	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust
TALC	14807-96-6	1% - 5%	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 20 mppcf if 1% Quartz or more; use Quartz limit
EPOXY RESIN	25068-38-6	1% - 5%	N/A	N/A
XYLENE(PURE)	1330-20-7	1% - 5%	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>
SYNTHETIC AMORPHOUS SILICA (PRECIPITATED)	112926-00-8	1% - 5%	N/A	TWA: 20 mppcf : (80)/(1% SiO <sub>2</sub> ) mg/m <sup>3</sup> TWA
ETHYLBENZENE	100-41-4	0% - 1%	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>

#### 4. FIRST AID MEASURES

##### First Aid Measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.
<b>Eye Contact</b>	Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open while rinsing. Call a physician immediately. If symptoms persist, call a physician.
<b>Skin Contact</b>	Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If not breathing, give artificial respiration. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist, call a physician.
<b>Ingestion</b>	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician immediately.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Use personal protective equipment as required.
<b>Most important symptoms and effects, both acute and delayed</b>	
<b>Most Important Symptoms and Effects</b>	No information available.
<b>Indication of any immediate medical attention and special treatment needed</b>	
<b>Notes to physician</b>	May cause sensitization of susceptible persons. Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### **Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** No information available.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact. Extremely flammable.

**Explosion Data**

**Sensitivity to Mechanical Impact** no data available.

**Sensitivity to Static Discharge** Yes.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures****Personal Precautions**

Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists. Ventilate the area.

**Environmental Precautions****Environmental Precautions**

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

**Methods and materials for containment and cleaning up****Methods for Containment**

Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later disposal.

**Methods for Cleaning Up**

Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

**7. HANDLING AND STORAGE****Precautions for safe handling****Advice on safe handling**

Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use with local exhaust ventilation. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe vapor or mist. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

**Conditions for safe storage, including any incompatibilities****Storage Conditions**

Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks and flame.

**Incompatible Products**

None known based on information supplied.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters****Exposure Guidelines**

Chemical Name	ACGIH	OSHA	NIOSH IDLH
METHYL AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
BARIUM SULFATE 7727-43-7	TWA: 5 mg/m <sup>3</sup> inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
STRONTIUM CHROMATE 7789-06-2	STEL: 0.0005 mg/m <sup>3</sup> Cr(VI) inhalable particulate matter TWA: 0.0002 mg/m <sup>3</sup> Cr(VI) inhalable particulate matter S*	TWA: 5 µg/m <sup>3</sup> Ceiling: 0.1 mg/m <sup>3</sup> CrO <sub>3</sub> applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect	IDLH: 15 mg/m <sup>3</sup> Cr(VI) TWA: 0.0002 mg/m <sup>3</sup> Cr
NATURAL WOLLASTONITE 13983-17-0	TWA: 1 mg/m <sup>3</sup> inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica	N/A	
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine, including engineered nanoscale
TALC 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust
XYLENE(PURE) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	
ETHYLBENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

NIOSH IDLH: Immediately Dangerous to Life or Health

### Exposure controls

#### Engineering Measures

Showers  
Eyewash stations  
Ventilation systems.

#### Individual protection measures, such as personal protective equipment

##### Eye/Face Protection

Use personal protective equipment as required.

##### Skin and Body Protection

Chemical resistant apron.

##### Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

#### Hygiene Measures

Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Physical state

Liquid

#### Appearance

Opaque

#### Odor

Solvent.

#### Odor Threshold

No data available

#### pH

No data available

#### Flash Point

-4 °F / -20 °C

#### Decomposition temperature

No data available

#### Boiling Point

133 °F / 56 °C

#### Melting Point / Melting Range

No data available

#### Freezing Point

No data available

Vapor Pressure @20°C (kPa) No data available  
 Vapor Density No data available  
 Bulk density No data available  
 Evaporation Rate No data available  
 Dynamic viscosity No data available

Partition coefficient: No data available  
 Density No data available  
 Specific Gravity 1.44  
 Water solubility No data available  
 Weight per Gallon (lbs/gal): 11.96  
 EPA VOC (lb/gal) 3

Flammability Limits in Air  
 Upper 0.18 %  
 Lower 0.03 %

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Conditions to Avoid

Extremes of temperature and direct sunlight.

### Incompatible Materials

None known based on information supplied.

### Hazardous Decomposition Products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Product Information** The product has not been tested

**Inhalation** There is no data for this product.

**Eye Contact** There is no data for this product.

**Skin Contact** There is no data for this product.

**Ingestion** There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL AMYL KETONE 110-43-0	= 1600 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit )	2000 - 4000 ppm ( Rat ) 6 h
BARIUM SULFATE 7727-43-7	= 307000 mg/kg ( Rat )	N/A	N/A
STRONTIUM CHROMATE 7789-06-2	= 811 mg/kg ( Rat )	N/A	N/A
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg ( Rat )	N/A	N/A
XYLENE(PURE) 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
ETHYLBENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.

**MUTAGENIC EFFECTS****Carcinogenicity**

No information available.

This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
STRONTIUM CHROMATE 7789-06-2	A1	Group 1	Known	X
NATURAL WOLLASTONITE 13983-17-0	N/A	Group 3	N/A	N/A
TITANIUM DIOXIDE 13463-67-7	N/A	Group 2B	N/A	X
TALC 14807-96-6	N/A	Group 2B Group 3	N/A	X
XYLENE(PURE) 1330-20-7	N/A	Group 3	N/A	N/A
SYNTHETIC AMORPHOUS SILICA (PRECIPITATED) 112926-00-8	N/A	Group 3	N/A	N/A
ETHYLBENZENE 100-41-4	A3	Group 2B	N/A	X

**Legend:**

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

A1 - Known Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Reproductive Toxicity**

No information available.

**Specific target organ systemic toxicity (single exposure)**

No information available.

**Specific target organ systemic toxicity (repeated exposure)**

No information available.

**Chronic Toxicity**

Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.

**Target Organ Effects**

Blood, Central nervous system (CNS), Central Vascular System (CVS), Eyes, Kidney, Liver, Lungs, Peripheral Nervous System (PNS), Respiratory system, Skin.

**Aspiration hazard**

No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 805 mg/kg

ATEmix (dermal) 14964 mg/kg

ATEmix (inhalation-dust/mist) 2.9 mg/l

Oral LD50 1844 mg/kg (rat) Estimated

Dermal LD50 22727 mg/kg (rat) Estimated

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
METHYL AMYL KETONE 110-43-0	N/A	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
ACETONE	N/A	4.74 - 6.33: 96 h Oncorhynchus	10294 - 17704: 48 h Daphnia

67-64-1		mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
TALC 14807-96-6	N/A	100: 96 h Brachydanio rerio g/L LC50 semi-static	N/A
XYLENE(PURE) 1330-20-7	N/A	13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50	0.6: 48 h Gammarus lacustris mg/L LC50 3.82: 48 h water flea mg/L EC50
ETHYLBENZENE 100-41-4	1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 9.6: 96 h Poecilia reticulata mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
METHYL AMYL KETONE 110-43-0	1.98
ACETONE 67-64-1	-0.24
XYLENE(PURE) 1330-20-7	3.15
ETHYLBENZENE 100-41-4	3.2

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Waste treatment methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**US EPA Waste Number**

D001

Chemical Name	RCRA - Basis for Listing	RCRA - D Series Wastes
ACETONE 67-64-1	Included in waste stream: F039	N/A
XYLENE(PURE) 1330-20-7	Included in waste stream: F039	N/A



ETHYLBENZENE 100-41-4	Included in waste stream: F039	N/A
--------------------------	--------------------------------	-----

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
STRONTIUM CHROMATE 7789-06-2	Toxic Corrosive Ignitable
ACETONE 67-64-1	Ignitable
XYLENE(PURE) 1330-20-7	Toxic Ignitable
ETHYLBENZENE 100-41-4	Toxic Ignitable

#### 14. TRANSPORT INFORMATION

##### DOT

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Special Provisions** 149, B52, IB2, T4, TP1, TP8, TP28  
**Description** UN1263, Paint, Marine Pollutant, 3, II, RQ  
**Emergency Response Guide Number** 128

##### TDG

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Description** UN1263, Paint, Marine Pollutant, 3, II

##### MEX

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Description** UN1263, Paint, 3, II

##### ICAO

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Special Provisions** A3, A72  
**Description** UN1263, Paint, 3, II

##### IATA

**UN-No** UN1263  
**Hazard class** 3  
**Packing Group** II  
**ERG Code** 3L  
**Special Provisions** A3, A72, A192

##### IMDG/IMO

**UN-No** UN1263  
**Hazard class** 3

**Packing Group** II  
**EmS-No** F-E, S-E  
**Special Provisions** 163, 367

**RID**

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Classification Code** F1  
**Description** UN1263, Paint, Environmentally Hazardous, 3, II

**ADR/RID**

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Classification Code** F1  
**Tunnel restriction code** (D/E)  
**Special Provisions** 163, 640C, 650, 367  
**Description** UN1263, Paint, Environmentally Hazardous, 3, II, (D/E)  
**ADR/RID-Labels** 3

**ADN**

**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Classification Code** F1  
**Special Provisions** 163, 640C, 650  
**Description** UN1263, Paint, Environmentally Hazardous, 3, II  
**Hazard Labels** 3  
**Limited Quantity (LQ)** 5 L  
**Ventilation** VE01

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
---------------	--------	-------------------------------

STRONTIUM CHROMATE	7789-06-2	0.1
XYLENE(PURE)	1330-20-7	1.0
ETHYLBENZENE	100-41-4	0.1

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CAA (Clean Air Act)**

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
STRONTIUM CHROMATE	7789-06-2	Present
XYLENE(PURE)	1330-20-7	Present
ETHYLBENZENE	100-41-4	Present

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
STRONTIUM CHROMATE	10 lb	X	N/A	X
XYLENE(PURE)	100 lb	N/A	N/A	X
ETHYLBENZENE	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
STRONTIUM CHROMATE	10 lb	N/A	RQ 10 lb final RQ RQ 4.54 kg final RQ
ACETONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE(PURE)	100 lb	N/A	RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYLBENZENE	1000 lb	N/A	RQ 1000 lb final RQ RQ 454 kg final RQ

**State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
STRONTIUM CHROMATE	7789-06-2	Carcinogen Developmental Female Reproductive Male Reproductive
TITANIUM DIOXIDE	13463-67-7	Carcinogen
ETHYLBENZENE	100-41-4	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
METHYL AMYL KETONE	X	X	X	N/A	N/A
BARIUM SULFATE	X	X	X	N/A	N/A

STRONTIUM CHROMATE	X	X	X	X	N/A
ACETONE	X	X	X	N/A	N/A
TITANIUM DIOXIDE	X	X	X	N/A	X
TALC	X	X	X	X	N/A
XYLENE(PURE)	X	X	X	X	N/A
SYNTHETIC AMORPHOUS SILICA (PRECIPITATED)	X	X	X	N/A	N/A
BUTYL ACETATE	X	X	X	N/A	N/A
ETHYLBENZENE	X	X	X	X	N/A

### International Regulations

#### Mexico - Grade

Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
METHYL AMYL KETONE	N/A	Mexico: TWA 50 ppm
BARIUM SULFATE	N/A	Mexico: TWA 10 mg/m <sup>3</sup>
STRONTIUM CHROMATE	A1 A2	Mexico: TWA 0.005 mg/m <sup>3</sup> Mexico: TWA 0.05 mg/m <sup>3</sup> Mexico: TWA 0.01 mg/m <sup>3</sup>
ACETONE	N/A	Mexico: TWA 500 ppm Mexico: STEL 750 ppm
TITANIUM DIOXIDE	N/A	Mexico: TWA 10 mg/m <sup>3</sup>
TALC	N/A	Mexico: TWA 2 mg/m <sup>3</sup> Mexico: STEL 2 mg/m <sup>3</sup>
XYLENE(PURE)	N/A	Mexico: TWA 100 ppm Mexico: STEL 150 ppm
ETHYLBENZENE	A3	Mexico: TWA 20 ppm

## 16. OTHER INFORMATION

#### NFPA

Health Hazard 2

Flammability 3

Instability 0

Physical and Chemical Hazards -

#### NFPA Rating



#### HMIS

Health Hazard 2 \*

Flammability 3

Physical Hazard 1

Personal protection X

Chronic Hazard Star Legend

\* Chronic Health Hazard

Issuing Date: 10-Jun-2021

Revision Date: 14-Jun-2021

#### Revision Note

No information available

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



# SAFETY DATA SHEET

Issuing Date: 10-Jun-2021

Revision Date: 14-Jun-2021

Print Date: 14-Jun-2021

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Name: E4E-100 ROADRUNNER B

PPI Tech  
 2700 W Cumberland St Bld 5 Lebanon, Pa 17042  
 Office: 717-814-7604  
 www.ppitechinc.com  
 orders@polyproindustry.com

professional users

## 2. HAZARDS IDENTIFICATION

### Classification

#### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

### Label Elements

#### Emergency Overview

**DANGER**

#### Hazard Statements

Causes serious eye irritation  
 May cause an allergic skin reaction  
 May cause drowsiness or dizziness  
 Highly flammable liquid and vapor



**Appearance** Opaque

**Physical state** Liquid

**Odor** Solvent

#### Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Contaminated work clothing should not be allowed out of the workplace  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/Bond container and receiving equipment  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection  
Keep cool

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
If skin irritation or rash occurs: Get medical advice/attention  
Wash contaminated clothing before reuse  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Call a POISON CENTER or doctor/physician if you feel unwell  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed  
Store in accordance with local regulations

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Hazards not otherwise classified (HNOC)**

#### **Other information**

- May be harmful if swallowed
- Harmful to aquatic life with long lasting effects
- Harmful to aquatic life

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### **There are no known carcinogenic chemicals in this product**

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
ACETONE	67-64-1	70% - 80%	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>
BENZYL ALCOHOL	100-51-6	1% - 5%	N/A	N/A
TRIETHYLENETETRAMINE(TETA)	112-24-3	0% - 1%	N/A	N/A

### **4. FIRST AID MEASURES**

#### **First Aid Measures**

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician. Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open while rinsing.
<b>Skin Contact</b>	Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a physician. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors.
<b>Ingestion</b>	Immediate medical attention is not required. Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Clean mouth with water and afterwards drink plenty of water. Never give

anything by mouth to an unconscious person. Consult a physician if necessary.

**Self-protection of the first aider** Remove all sources of ignition. Use personal protective equipment as required.

**Most important symptoms and effects, both acute and delayed**

**Most Important Symptoms and Effects** No information available.

**Indication of any immediate medical attention and special treatment needed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** No information available.

**Specific hazards arising from the chemical**

Extremely flammable.

**Explosion Data**

**Sensitivity to Mechanical Impact** no data available.

**Sensitivity to Static Discharge** Yes.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists. Ventilate the area.

**Environmental Precautions**

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

**Methods and materials for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning Up** Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling** Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use with local exhaust

ventilation. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe vapor or mist. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

#### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks and flame.

**Incompatible Products** None known based on information supplied.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH	OSHA	NIOSH IDLH
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>

NIOSH IDLH: *Immediately Dangerous to Life or Health*

#### Exposure controls

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems.

#### Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Use personal protective equipment as required.

**Skin and Body Protection** Chemical resistant apron.

**Respiratory Protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene Measures** Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	Liquid	<b>Appearance</b>	Opaque
<b>Odor</b>	Solvent.	<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available	<b>Flash Point</b>	-4 °F / -20 °C
<b>Decomposition temperature</b>	No data available	<b>Boiling Point</b>	133 °F / 56 °C
<b>Melting Point / Melting Range</b>	No data available	<b>Freezing Point</b>	No data available
<b>Vapor Pressure @20°C (kPa)</b>	No data available	<b>Partition coefficient:</b>	No data available
<b>Vapor Density</b>	No data available	<b>Density</b>	No data available
<b>Bulk density</b>	No data available	<b>Specific Gravity</b>	0.84
<b>Evaporation Rate</b>	No data available	<b>Water solubility</b>	No data available
<b>Dynamic viscosity</b>	No data available	<b>Weight per Gallon (lbs/gal):</b>	7.04
		<b>EPA VOC (lb/gal)</b>	1
<b>Flammability Limits in Air</b>			
<b>Upper</b>	0 %		
<b>Lower</b>	0 %		



## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Conditions to Avoid

Extremes of temperature and direct sunlight.

### Incompatible Materials

None known based on information supplied.

### Hazardous Decomposition Products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	The product has not been tested
<b>Inhalation</b>	There is no data for this product.
<b>Eye Contact</b>	There is no data for this product.
<b>Skin Contact</b>	There is no data for this product.
<b>Ingestion</b>	There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
BENZYL ALCOHOL 100-51-6	= 1230 mg/kg ( Rat )	= 2 g/kg ( Rabbit )	= 8.8 mg/L ( Rat ) 4 h
TRIETHYLENETETRAMINE(TETA) 112-24-3	= 2500 mg/kg ( Rat )	= 550 mg/kg ( Rabbit )	N/A

### Information on toxicological effects

**Symptoms** No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Sensitization</b>	No information available.
<b>MUTAGENIC EFFECTS</b>	No information available.
<b>Carcinogenicity</b>	No information available.
<b>Legend:</b>	
<b>Reproductive Toxicity</b>	No information available.
<b>Specific target organ systemic toxicity (single exposure)</b>	No information available.
<b>Specific target organ systemic toxicity (repeated exposure)</b>	No information available.
<b>Chronic Toxicity</b>	Avoid repeated exposure.
<b>Target Organ Effects</b>	Central nervous system (CNS), Eyes, Respiratory system, Skin.
<b>Aspiration hazard</b>	No information available.

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	4988 mg/kg
<b>ATEmix (dermal)</b>	11992 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	31.9 mg/l

Oral LD50  
Dermal LD50

6506 mg/kg (rat) Estimated  
12739 mg/kg (rat) Estimated

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
ACETONE 67-64-1	N/A	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
BENZYL ALCOHOL 100-51-6	N/A	10: 96 h Lepomis macrochirus mg/L LC50 static 460: 96 h Pimephales promelas mg/L LC50 static	23: 48 h water flea mg/L EC50
TRIETHYLENETETRAMINE(TETA) 112-24-3	2.5: 72 h Desmodesmus subspicatus mg/L EC50 20: 72 h Pseudokirchneriella subcapitata mg/L EC50 3.7: 96 h Pseudokirchneriella subcapitata mg/L EC50	495: 96 h Pimephales promelas mg/L LC50 570: 96 h Poecilia reticulata mg/L LC50 semi-static	31.1: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

Chemical Name	Partition coefficient
ACETONE 67-64-1	-0.24
BENZYL ALCOHOL 100-51-6	1.1
TRIETHYLENETETRAMINE(TETA) 112-24-3	-1.4

### Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### Waste treatment methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

#### US EPA Waste Number

D001

Chemical Name	RCRA - Basis for Listing	RCRA - D Series Wastes
ACETONE 67-64-1	Included in waste stream: F039	N/A

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ACETONE 67-64-1	Ignitable

## 14. TRANSPORT INFORMATION

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Special Provisions</b>	149, B52, IB2, T4, TP1, TP8, TP28
<b>Description</b>	UN1263, Paint, 3, II, RQ
<b>Emergency Response Guide Number</b>	128

**TDG**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1263, Paint, 3, II

**MEX**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1263, Paint, 3, II

**ICAO**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Special Provisions</b>	A3, A72
<b>Description</b>	UN1263, Paint, 3, II

**IATA**

<b>UN-No</b>	UN1263
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>ERG Code</b>	3L
<b>Special Provisions</b>	A3, A72, A192

**IMDG/IMO**

<b>UN-No</b>	UN1263
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>EmS-No</b>	F-E, S-E
<b>Special Provisions</b>	163, 367

**RID**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Classification Code</b>	F1
<b>Description</b>	UN1263, Paint, 3, II

**ADR/RID**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Classification Code</b>	F1
<b>Tunnel restriction code</b>	(D/E)
<b>Special Provisions</b>	163, 640C, 650, 367

**Description** UN1263, Paint, 3, II, (D/E)  
**ADR/RID-Labels** 3

**ADN**

**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Classification Code** F1  
**Special Provisions** 163, 640C, 650  
**Description** UN1263, Paint, 3, II  
**Hazard Labels** 3  
**Limited Quantity (LQ)** 5 L  
**Ventilation** VE01

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**CAA (Clean Air Act)**

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

**Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive

Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
ACETONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ

### State Regulations

#### California Proposition 65

This product does not contain any Proposition 65 chemicals

### U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
ACETONE	X	X	X	N/A	N/A
TRIETHYLENETETRAMINE (TETA)	X	X	X	N/A	N/A

### International Regulations

Mexico - Grade Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
ACETONE	N/A	Mexico: TWA 500 ppm Mexico: STEL 750 ppm

## 16. OTHER INFORMATION

**NFPA** Health Hazard 2 Flammability 3 Instability 0 Physical and Chemical Hazards -

NFPA Rating



**HMIS** Health Hazard 1 \* Flammability 3 Physical Hazard 0 Personal protection X

Chronic Hazard Star Legend

\* Chronic Health Hazard

Issuing Date: 10-Jun-2021

Revision Date: 14-Jun-2021

Revision Note

No information available

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. AD2298-FD