

E4E SUPER POLY - Low Odor Polyaspartic 86% solids

SECTION 1. IDENTIFICATION			
Product identifier	E4E SUPER POLY - Low odor Polyaspartic 86% solids		
Other Means of	N. A		
<u>Identification</u>			
Recommended Use	Polyurea coating		
Restrictions on Use	Unknown		
Supplier Identifier	EPOXY DEPOT 235 W. Penn Avenue Cleona, PA 17042 855-723-7699		
24-hr No.	855-723-7699		

SECTION 2. HAZARD IDENTIFICATION

Classification Acute toxicity Oral and Dermal Category 4

Skin Irritation Category 2

Serious eye damage/ eye irritation Category 1

Skin sensitization Category 1

Specific Target Organ Toxicity - Repeated Exposure Category 1

Pyrophoric Liquids Category 1

Label Elements





Signal Word

Danger

Hazard Statements

H302 + H312: Harmful if swallowed or in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H361: Suspected of damaging fertility or the unborn child.

Precautionary statements

Prevention:

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P261: Avoid breathing vapors, mist, or spray.

P264: Wash hands, forearms, and other exposed areas thoroughly after handling.

Product Identifier: E4E SUPER POLY - Low odor Polyaspartic 86% solids

Page 1 of 7



SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS			
Chemical Name	CAS No.	% By Weight	Other Identifiers LD 50 (ORAL-RAT) (mg/kg)
Homopolymer of HDI	28182-81-2	45 - 80	>5000
Hexamethylene diisocyanate	822-06-0	0.1 - 15	746

Notes:

Not applicable

P270: Do not eat drink or smoke when using this product.

P272: Contaminated work clothing must not be allowed out of the workplace.

P280: Wear protective gloves, protective clothing, and eye protection

P402+405+ P235: Store locked in a cool and dry location.

P411: Store in temperatures not exceeding freezing point.

P391: Collect Spillage

P501: Dispose of contents/container in accordance with local, regional, national,

territorial, provincial, and international regulations.

Response: Handle in accordance with good industrial hygiene and safety practice.

P308 + P313: if exposed or concerned: Get medical advice / attention.

P310: Immediately call a poison center or doctor.

P330: Rinse mouth.

P302 + P352: if on skin: Wash with plenty of water

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P313 + P333 +P337: Get medical advice/attention: If skin irritation or rash occurs or If

eye irritation persists

Other Hazards: Keep away from children and animals

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation:

Remove patient to fresh air. Give mouth to mouth if patient is not breathing. Seek medical attention immediately.

Skin Contact:

Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

Ingestion:

Do not induce vomiting unless directed to do so by medical personnel. Give two glasses of water for dilution. Never give anything by mouth to an unconscious person. Immediately consult a physician

Most Important Symptoms and Effects, Acute and Delayed

If inhaled:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

If on skin:

Product Identifier: E4E SUPER POLY - Low odor Polyaspartic 86% solids

Page 2 of 7



Harmful if in contact with the skin. Causes skin irritation. Exposure may produce an allergic reaction

If in eyes:

Causes serious eye damage.

If Ingested:

Ingestion is likely to be harmful or have adverse effects

Immediate Medical Attention and Special Treatment:

Special Instructions:

If a physician or medical attention is required, have product container or label at hand.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, appropriate foam, water spray, dry chemical powder.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Product

Ammonia gas may be liberated at high temperatures. In case of incomplete combustion an increased formation of oxides of nitrogen (NOx) is to be expected. Incomplete combustion may form carbon monoxide. May generate ammonia gas. May generate toxic nitrogen oxide gases. Burning produces noxious and toxic fumes. Downwind personnel must be evacuated. Refer to section 9 for flammability properties.

Special Protective Equipment and Precautions for Fire-fighters

Use self-contained breathing apparatus and protective clothing

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

As a general precaution, take personal precaution not to breath gas, vapors, or dusts. Do not get in eyes, on skin or clothing.

Use appropriate personal protection equipment. In the event of an emergency, evacuate any unnecessary personnel.

As an environmental precaution, prevent spillage to sewers, public waters, and do not penetrate ground/soil.

Methods and Materials for Containment and Clean up

For containment, ensure adequate ventilation and absorb any spill with inert liquid binding material and dispose of waste safely.

Product Identifier: E4E SUPER POLY - Low odor Polyaspartic 86% solids



SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Handle in accordance to good industrial hygiene and safety procedures. Wear respiratory protection when handling. Avoid body contact of containers or contents unless wearing appropriate personal protective equipment. Wear respiratory protection when handling. Avoid release into the environment.

Conditions for Safe Storage

Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incapable materials.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation.

Data not available. For additional information, please consult the corresponding requirements under http://www.ccohs.ca/topics/hazards/chemicals/

	ACGIH® TLV®		OSHA PEL		AIHA® WEEL®	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term

Appropriate Engineering Controls

Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

Individual Protection Measures









General Measures

Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

Eve / Face Protection

Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

Skin Protection

Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

Respiratory Protection

Product Identifier: E4E SUPER POLY - Low odor Polyaspartic 86% solids



If insufficient ventilation, wear respiratory protection.

SECTION 9. PHYSICAL AND CHEMICAL P	ROPERTIES
Appearance	Clear Liquid
Odor	Not available
Odor threshold	Not available
pH	Not available
Melting Point	Not available
Initial Boiling Point / Range	Approximately 104°C
Flash point	>194
Evaporation rate	Not available
Flammability(solid; gas)	Not available
Lower flammable/explosive limit	Not available
Upper flammable/explosive limit	Not available
Vapor pressure	Butyle acétate: 15 @ 20°C
	Isocyanate : 5.2 x 10 ⁻⁹ @ 20°C
Vapor density	Not available
Specific gravity	1.14
Solubility	Insoluble. Reacts slowly with water to
	liberate CO₂ gas.
Partition coefficient – n- Octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available

SECTION 10. STABILITY AND REACTIVITY	
Reactivity	None known
Chemical stability	Stable under recommended handling and storage conditions
Possibility of Hazardous reactions	In presence of moisture and when in contact with other materials that react with isocyanates, or temperatures above 177 °C may cause polymerization. Avoid heat, sparks, and flame.
Conditions to avoid	Direct sunlight. Extremely high and low temperatures.
Incompatible materials	Water, amines, strong acids and bases, alcohols, and copper alloys.
Hazardous decomposition products	Nitrogen oxides, carbon oxides.

SECTION 11. TOXICOLOGY INFORMATION
Likely Routes of Administration
Inhalation, skin contact, eye contact, ingestion.
Acute Toxicity

Product Identifier: E4E SUPER POLY - Low odor Polyaspartic 86% solids



Oral: Harmful if swallowed.

Dermal: Harmful in contact with skin.

LD50 and LC50 Data

Not available

Skin Corrosion/Irritation

Causes skin irritation.

Serious Eye Damage/Irritation

Causes serious eye damage

STOT (Specific Target Organ Toxicity) – Single Exposure Inhalation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Aspiration Hazard

Not classified based on available data.

STOT(Specific Target Organ Toxicity) - Repeated Exposure

Skin, eyes, central nervous system, respiratory system

Respiratory and/or Skin Sensitization

May irritate mucous membranes, eyes, nose, and respiratory passages. May cause asthma attack to persons with pre-existing bronchial hyper reactivity. Exposure to high concentrations may lead to bronchitis, bronchial spasm and pulmonary oedema. Effects are usually reversible. May cause C.N.S. depression with symptoms of nausea, light-headedness, drowsiness, dizziness, loss of coordination

Carcinogenicity

Unknown

Chemical Name	IARC	ACGIH [®]	NTP	OSHA

Reproductive Toxicity

Suspected of damaging fertility or the unborn child.

Germ Cell Mutagenicity

Not classified

Interactive Effects

Not classified

SECTION 12. ECOLOGICAL INFORMATION

This is not required by WHMIS

This is not required by OSHA HCS 2012

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations

Product Identifier: E4E SUPER POLY - Low odor Polyaspartic 86% solids

Page 6 of 7



SECTION 15. REGULATORY INFORMATION

Not required under Canadian Regulations.

SECTION 16. OTHER INFORMATION			
Date of Preparation	November 18, 2016		
Date of Last Revision	January 4, 2023		
Revision Indicators	The entire MDSD was changed on November 18, 2016 to be in accordance with the WHMIS 2015 which incorporate the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces.		
References	1. CHOHS Fact Sheets September 2016 ©CCOHS 2016		
	Supplier's Material Safety Data Sheet(s)		

<u>Notice:</u> The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that E4E will not be liable for any damages resulting from its use since E4E cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.

Product Identifier: E4E SUPER POLY - Low odor Polyaspartic 86% solids