



E4E-100-VRM-Fastcure B

SECTION 1. IDENTIFICATION

Product identifier	E4E-100-VRM-Fastcure B
Other Means of Identification	None
Recommended Use	Epoxy hardener, Fastcure applications
Restrictions on Use	Unknown
Supplier Identifier	Polypro Industry 2700 Cumberland street building 5 Lebanon PA, 17042
Emergency Phone No.	717-454-6556

SECTION 2. HAZARD IDENTIFICATION

Classification	Acute Toxicity, Oral (Category 4) Acute Toxicity, Dermal (Category 5) Skin Sensitization (Category 1A) Skin Corrosion/irritation (Category 1B) Serious eye damage/irritation (Category 1) Reproductive toxicity (Category 2) Hazardous to the aquatic environment - acute (Category 1) Hazardous to the aquatic environment - chronic (Category 1)
-----------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Label Elements



Signal Word

Danger

Hazard Statements

- H227 Combustible liquid
- H302 Harmful if swallowed
- H312 Harmful in contact with skin
- H317 May cause an allergic skin reaction
- H314 Causes severe skin burns and eye damage
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H335 May cause respiratory irritation
- H360 May cause harm to breast-fed children
- H361 May damage the unborn child. Suspected of damaging fertility
- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects

Precautionary statements



Safety Data Sheet

Prevention:

P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P260 Do not breathe dust or mist. P263 Avoid contact during pregnancy/while nursing. P264 Wash with plenty of water and soap thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P284 Wear respiratory protection. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. P310 Immediately call a POISON CENTER or doctor/physician. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P341 + P311 IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P362 + P364 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use water spray, dry powder, or foam for extinction. P233 Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards: Unknown

GHS Special Labeling: EUH205 - "Contains epoxy constituents. May produce a skin allergy."

SECTION 3. COMPOSITION

Chemical Name	CAS No.	% concentration
epoxy adduct	Proprietary	1 - 10 %
isophorone diamine	2855-13-2	10 - 20 %
benzyl alcohol	100-51-6	1 - 10 %
4-nonylphenol, branched	84852-15-3	10 - 20 %
polyoxypropylene diamine	9046-10-0	15 - 25 %
amine curing agent	Mixture	35 - 55 %

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Skin Contact:

Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

Ingestion:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Most Important Symptoms and Effects, Acute and Delayed

Burning pain and severe corrosive skin damage. Can burn mouth, throat, and stomach. Can cause severe irritation and burns to the respiratory tract. May cause an allergic respiratory reaction. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Immediate Medical Attention and Special Treatment:

Provide general supportive measures and treat symptomatically. Chemical burns: Flush



Safety Data Sheet

with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO₂)

Unsuitable Extinguishing Media

water jet

Specific Hazards Arising from the Product

During fire, nitrous gases, fumes/smoke, isocyanates and vapour may be formed.

Special Protective Equipment and Precautions for Fire-fighters

Self-contained breathing apparatus and turn-out gear must be worn in case of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillage cannot be contained. For personal protection, see section 8 of the SDS.

Methods and Materials for Containment and Clean up

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust or mist. Do not get in eyes, on skin, or on clothing. Do not get this material in contact with eyes. Do not taste or swallow. When using, do not eat, drink or smoke. Provide adequate ventilation. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Keep away from sources of ignition -No smoking. Take precautionary measures against static discharge.



Safety Data Sheet

Conditions for Safe Storage

Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incompatible materials.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation.

Data not available. For additional information, please consult the corresponding requirements under <http://www.ccohs.ca/topics/hazards/chemical/chemicals/>

Appropriate Engineering Controls

Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

Individual Protection Measures



General Measures

Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

Eye / Face Protection

Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

Skin Protection

Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

Respiratory Protection

If insufficient ventilation, wear respiratory protection.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Transparent yellow
Odor	Slight amine odor
Odor threshold	Not available
pH	Not available
Melting Point	Not available
Initial Boiling Point / Range	Not available
Flash point	>53 C
Evaporation rate	Not available
Flammability(solid; gas)	Not available
Lower flammable/explosive limit	Not available
Upper flammable/explosive limit	Not available



Safety Data Sheet

Vapor pressure	Not available
Vapor density	Not available
Specific gravity	Not available
Solubility	Partial
Partition coefficient – n- Octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	800 – 900 cps

SECTION 10. STABILITY AND REACTIVITY

Reactivity	Non-reactive
Chemical stability	Stable under recommended handling and storage conditions
Possibility of Hazardous reactions	This product will polymerize if mixed with an epoxy resin. Considerable heat can evolve.
Conditions to avoid	Avoid temperatures exceeding the flash point. Epoxy resins under uncontrolled conditions.
Incompatible materials	Strong oxidizing agents and acids.
Hazardous decomposition products	Unknown

SECTION 11. TOXICOLOGY INFORMATION

Likely Routes of Administration

Inhalation, skin contact, eye contact, ingestion.

Acute Toxicity

Oral: Harmful if swallowed.

Dermal: Harmful in contact with skin.

LD50 and LC50 Data

Not available

Skin Corrosion/Irritation

Causes skin irritation.

Serious Eye Damage/ Irritation

Causes serious eye damage

STOT (Specific Target Organ Toxicity) – Single Exposure Inhalation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Aspiration Hazard

Not classified based on available data.

STOT(Specific Target Organ Toxicity) – Repeated Exposure

Skin, eyes, central nervous system, respiratory system

Respiratory and/or Skin Sensitization

No data

Carcinogenicity

Unknown

Reproductive Toxicity

Not available

Germ Cell Mutagenicity

Product Identifier: E4E-100-VRM-Fastcure

Page 5 of 7



Safety Data Sheet

Not available

Interactive Effects

Not available

SECTION 12. ECOLOGICAL INFORMATION

Toxic to aquatic life with lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

SECTION 14. TRANSPORT INFORMATION

UN Number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations:

UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime):

UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):

UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III

SECTION 15. REGULATORY INFORMATION

Safety/health Canadian regulations specifics: Refer to section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).

SECTION 16. OTHER INFORMATION

Date of Preparation August 2020

Date of Last Revision June 1, 2014

Revision Indicators The entire MSDS was change in August 2020 to be in accordance with the WHMIS 2015 which incorporates the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces.

References

1. CHOHS Fact Sheets September 2016 ©CCOHS 2016
2. Supplier's Material Safety Data Sheet(s)

ACGIH	American Conference of Governmental Industrial Hygienists
ATE	Acute toxicity estimate
CAS	Chemical Abstract Service
DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods Code
LC	Lethal concentration
LD	Lethal Dosage
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)

Product Identifier: E4E-100-VRM-Fastcure

Page 6 of 7

B Date of Preparation: August 2020



Safety Data Sheet

PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TDG	Transport of dangerous goods in Canada
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System

Notice: The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that Sealchem will not be liable for any damages resulting from its use since Sealchem cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.