

Polyurea Crack Filler - A

Product identifier	Polyurea Crack Filler - A	
Other Means of	N. A	
Identification		
Recommended Use	Polyurethane adhesive	
Restrictions on Use	Unknown	
Supplier Identifier	PPI Tech Inc 2700 Cumberland St Ste 5 Lebanon, PA 17042 Office: (717)847-7604	

SECTION 2. HAZARD IDENTIFICATION

<u>Classification</u> Flammable liquid Category 4

Carcinogen Category 2
Aspiration Hazard Category 1

Serious eye damage/eye irritation Category 2A

Skin Sensitization Category 1

Label Elements







Signal Word

Danger

Hazard Statements

H304: May be fatal if swallowed and enters airways.

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H351: Suspected of causing cancer.

Precautionary statements

Prevention:

P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion proof electrical/ventilating/lighting equipment. P242 Use only non-sparking tools. P243 Take action to prevent static discharge. P280 Wear protective gloves/protective clothing/eye protection/face protection. P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P264 Wash hands thoroughly after handling. P272 Contaminated work clothing must not be allowed out of the workplace. P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 Do NOT induce vomiting.

Product Identifier: Polyurea Crack Filler - A

Page 1 of 8



P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/attention. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P308 + P313 If exposed or concerned: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use foam, dry chemical, water spray or carbon dioxide (CO2) to extinguish P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards: Unknown

Chemical Name	CAS No.	% concentration
Heavy aromatic solvent naphtha, petroleum	64742-94-5	40-60 %
Tetrahydroxypropylethylendiamine	102-60-3	40-60%

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation:

IF INHALED: Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to mouth resuscitation.

Skin Contact:

Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

Ingestion:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Most Important Symptoms and Effects, Acute and Delayed

If inhaled:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

If on skin:

Harmful if in contact with the skin. Causes skin irritation. Exposure may produce an allergic reaction

If in eyes:

Causes serious eve damage.

If Ingested:

Ingestion is likely to be harmful or have adverse effects

Immediate Medical Attention and Special Treatment:

Special Instructions:

If a physician or medical attention is required, have product container or label at hand.

Product Identifier: Polyurea Crack Filler - A Page 2 of 8



SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO2)

Unsuitable Extinguishing Media

Do not use water jet as it might spread flame.

Specific Hazards Arising from the Product

During fire, nitrous gases, fumes/smoke, isocyanates and vapour may be formed. Combustion products may include: acidic hydrogen chloride & hydrogen fluoride, carbon oxide, hydrocarbons, nitrogen oxides and smoke.

Special Protective Equipment and Precautions for Fire-fighters

Flammable. Evacuate area. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect personnel attempting to stop a leak. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Use water spray to cool fire exposed surfaces and to protect personnel. Self-contained breathing apparatus and turn-out gear must be worn in case of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

As a general precaution, take personal precaution not to breath gas, vapors, or dusts. Do not get in eyes, on skin or clothing.

Use appropriate personal protection equipment. In the event of an emergency, evacuate any unnecessary personnel.

As an environmental precaution, prevent spillage to sewers, public waters, and do not penetrate ground/soil.

Methods and Materials for Containment and Clean up

For containment, ensure adequate ventilation and absorb any spill with inert liquid binding material and dispose of waste safely.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Handle in accordance to good industrial hygiene and safety procedures. Wear respiratory protection when handling. Avoid body contact of containers or contents unless wearing appropriate personal protective equipment. Wear respiratory protection when handling. Avoid release into the environment.

Conditions for Safe Storage

Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incapable materials.

Product Identifier: Polyurea Crack Filler - A Page 3 of 8



SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation.

Data not available. For additional information, please consult the corresponding requirements under http://www.ccohs.ca/topics/hazards/chemical/chemicals/

	ACGIH® TLV®		OSHA PEL		AIHA® WEEL®	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term

Appropriate Engineering Controls

Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

Individual Protection Measures









General Measures

Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

Eye / Face Protection

Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

Skin Protection

Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

Respiratory Protection

If insufficient ventilation, wear respiratory protection.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES			
Appearance	Black Liquid		
Odor	Not available		
Odor threshold	Not available		
pH	Not available		
Melting Point	Not available		
Initial Boiling Point / Range	Not available		
Flash point	Not available		
Evaporation rate	Not available		
Flammability(solid; gas)	Not available		

Product Identifier: Polyurea Crack Filler - A



Lower flammable/explosive limit	Not available
Upper flammable/explosive limit	Not available
Vapor pressure	Not available
Vapor density	Not available
Specific gravity	0.95
Solubility	Insoluble
Partition coefficient – n- Octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available

Product Identifier: Polyurea Crack Filler - A



SECTION 10. STABILITY AND REACTIVIT	Υ
Reactivity	Non-reactive
Chemical stability	Stable under recommended handling and storage conditions
Possibility of Hazardous reactions	Risk of bursting. Reacts with alcohols. Reacts with acids. Reacts with alkalies. Reacts with amines. Risk of exothermic reaction.
Conditions to avoid	Keep away from heat, sparks and open flame. Avoid high temperatures. Avoid contact with incompatible materials.
Incompatible materials	Water, amines, substances that react to polyurea
Hazardous decomposition products	unknown

SECTION 11. TOXICOLOGY INFORMATION

Likely Routes of Administration

Inhalation, skin contact, eye contact, ingestion.

Acute Toxicity

Oral: Harmful if swallowed.

Dermal: Harmful in contact with skin.

LD50 and LC50 Data

Not available

Skin Corrosion/Irritation

Causes skin irritation.

Serious Eye Damage/Irritation

Causes serious eye damage

STOT (Specific Target Organ Toxicity) - Single Exposure Inhalation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Aspiration Hazard

Not classified based on available data.

STOT(Specific Target Organ Toxicity) - Repeated Exposure

Skin, eyes, central nervous system, respiratory system

Respiratory and/or Skin Sensitization

May irritate mucous membranes, eyes, nose, and respiratory passages. May cause asthma attack to persons with pre-existing bronchial hyper reactivity. Exposure to high concentrations may lead to bronchitis, bronchial spasm and pulmonary oedema.

Product Identifier: Polyurea Crack Filler - A

Page 6 of 8



Effects are usually reversible. May cause C.N.S. depression with symptoms of nausea, light-headedness, drowsiness, dizziness, loss of coordination

Carcinogenicity

Unknown

Chemical Name | IARC | ACGIH® | NTP | OSHA

Reproductive Toxicity

Not available

Germ Cell Mutagenicity

Not available

Interactive Effects

Not available

SECTION 12. ECOLOGICAL INFORMATION

Non-hazardous to aquatic environment.

This is not required by WHMIS

This is not required by OSHA HCS 2012

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14. TRANSPORT INFORMATION
DOT (U.S) UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime):
UN1268; N.O.S : Petroleum distillats, CLASS 3; PG III; Yes
UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air): UN1263; Combustible PAINT RELATED MATERIAL; CLASS 3; PG III

SECTION 15. REGULATORY INFORMATION

Product Identifier: Polyurea Crack Page 7 of 8

Filler - A Date of last revision:



SECTION 16. OTHER INFORMATION				
Date of Preparation	January 4, 2023			
Date of Last Revision	January 4, 2023			
Revision Indicators				
References				

<u>Notice:</u> The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that American Resins will not be liable for any damages resulting from its use since American Resins cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.

Product Identifier: Polyurea Crack Filler - A Page 8 of 8



Polyurea Crack Filler - B

SECTION 1. IDENTIFICATION		
Product identifier	Polyurea Crack Filler - B	
Other Means of Identification	N. A	
Recommended Use	Polyurethane adhesive	
Restrictions on Use	Unknown	
Supplier Identifier	PPI Tech Inc 2700 Cumberland St Ste 5 Lebanon, PA 17042 Office: (717)847-7604	

SECTION 2. HAZARD IDENTIFICATION

<u>Classification</u> Flammable liquid Category 3

Carcinogen Category 1B Aspiration Hazard Category 1

Serious eye damage/eye irritation Category 2A

Skin Sensitization Category 1

Label Elements







Signal Word

Danger

Hazard Statements

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H319: Causes serious eve irritation.

H317: May cause an allergic skin reaction.

H351: Suspected of causing cancer.

Precautionary statements

Prevention:

P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion proof electrical/ventilating/lighting equipment. P242 Use only non-sparking tools. P243 Take action to prevent static discharge. P280 Wear protective gloves/protective clothing/eye protection/face protection. P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P264 Wash hands thoroughly after handling. P272 Contaminated work clothing must not be allowed out of the workplace. P301 + P310 IF

Product Identifier: Polyurea Crack Filler - B

Page 1 of 8



SWALLOWED: Immediately call a POISON CENTER/doctor. P331 Do NOT induce vomiting. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/attention. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P308 + P313 If exposed or concerned: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use foam, dry chemical, water spray or carbon dioxide (CO2) to extinguish P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards: Unknown

Chemical Name	CAS No.	% concentration
Light aromatic solvent naphtha, petroleum	64742-95-6	20-30 %
Diphenylmethanediisocyanate polymeric	9016-87-9	35-50
4,4'-methylenediphenyl diisocyanate	101-68-8	20-35

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation:

IF INHALED: Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to mouth resuscitation.

Skin Contact:

Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

Ingestion:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Most Important Symptoms and Effects, Acute and Delayed

If inhaled:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

If on skin:

Harmful if in contact with the skin. Causes skin irritation. Exposure may produce an allergic reaction

If in eyes:

Causes serious eye damage.

If Ingested:

Ingestion is likely to be harmful or have adverse effects

Immediate Medical Attention and Special Treatment:

Product Identifier: Polyurea Crack Filler - B Page 2 of 8



If a physician or medical attention is required, have product container or label at hand.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO2)

Unsuitable Extinguishing Media

Do not use water jet as it might spread flame.

Specific Hazards Arising from the Product

During fire, nitrous gases, fumes/smoke, isocyanates and vapour may be formed. Combustion products may include: acidic hydrogen chloride & hydrogen fluoride, carbon oxide, hydrocarbons, nitrogen oxides and smoke.

Special Protective Equipment and Precautions for Fire-fighters

Flammable. Evacuate area. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect personnel attempting to stop a leak. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Use water spray to cool fire exposed surfaces and to protect personnel. Self-contained breathing apparatus and turn-out gear must be worn in case of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

As a general precaution, take personal precaution not to breath gas, vapors, or dusts. Do not get in eyes, on skin or clothing.

Use appropriate personal protection equipment. In the event of an emergency, evacuate any unnecessary personnel.

As an environmental precaution, prevent spillage to sewers, public waters, and do not penetrate ground/soil.

Methods and Materials for Containment and Clean up

For containment, ensure adequate ventilation and absorb any spill with inert liquid binding material and dispose of waste safely.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Handle in accordance to good industrial hygiene and safety procedures. Wear respiratory protection when handling. Avoid body contact of containers or contents unless wearing appropriate personal protective equipment. Wear respiratory protection when handling. Avoid release into the environment.

Conditions for Safe Storage

Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incapable materials.

Product Identifier: Polyurea Crack Filler - B Page 3 of 8



SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation.

Data not available. For additional information, please consult the corresponding requirements under http://www.ccohs.ca/topics/hazards/chemical/chemicals/

	ACGIH® TLV®		OSHA PEL		AIHA® WEEL®	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term

Appropriate Engineering Controls

Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

Individual Protection Measures









General Measures

Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

Eye / Face Protection

Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

Skin Protection

Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

Respiratory Protection

If insufficient ventilation, wear respiratory protection.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES			
Appearance	Dark amber Liquid		
Odor	Not available		
Odor threshold	Not available		
рН	Not available		
Melting Point	Not available		
Initial Boiling Point / Range	N. A		
Flash point	N. A		
Evaporation rate	Not available		
Flammability(solid; gas)	Not available		

Product Identifier: Polyurea Crack Filler - B

Page 4 of 8



Lower flammable/explosive limit	Not available
Upper flammable/explosive limit	Not available
Vapor pressure	Not available
Vapor density	Not available
Specific gravity	1.13
Solubility	Insoluble
Partition coefficient – n-	Not available
Octanol/water	
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available

SECTION 10. STABILITY AND REACTIVITY	
Reactivity	Non-reactive
Chemical stability	Stable under recommended handling
	and storage conditions
Possibility of Hazardous reactions	Risk of bursting. Reacts with alcohols. Reacts with acids. Reacts with alkalies. Reacts with amines. Risk of exothermic reaction.
Conditions to avoid	Keep away from heat, sparks and open flame. Avoid high temperatures. Avoid contact with incompatible materials.
Incompatible materials	Water, amines, substances that react to polyurea
Hazardous decomposition products	unknown

Product Identifier: Polyurea Crack Filler - B



SECTION 11. TOXICOLOGY INFORMATION

Likely Routes of Administration

Inhalation, skin contact, eye contact, ingestion.

Acute Toxicity

Oral: Harmful if swallowed.

Dermal: Harmful in contact with skin.

LD50 and LC50 Data

Not available

Skin Corrosion/Irritation

Causes skin irritation.

Serious Eye Damage/Irritation

Causes serious eye damage

STOT (Specific Target Organ Toxicity) - Single Exposure Inhalation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Aspiration Hazard

Not classified based on available data.

STOT(Specific Target Organ Toxicity) - Repeated Exposure

Skin, eyes, central nervous system, respiratory system

Respiratory and/or Skin Sensitization

May irritate mucous membranes, eyes, nose, and respiratory passages. May cause asthma attack to persons with pre-existing bronchial hyper reactivity. Exposure to high concentrations may lead to bronchitis, bronchial spasm and pulmonary oedema.

Product Identifier: Polyurea Crack Filler - B



Effects are usually reversible. May cause C.N.S. depression with symptoms of nausea, light-headedness, drowsiness, dizziness, loss of coordination **Carcinogenicity**

Unknown

Chemical Name	IARC	ACGIH [®]	NTP	OSHA

Reproductive Toxicity
Not available
Germ Cell Mutagenicity
Not available
Interactive Effects

Not available

SECTION 12. ECOLOGICAL INFORMATION

Non-hazardous to aquatic environment.

This is not required by WHMIS

This is not required by OSHA HCS 2012

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14. TRANSPORT INFORMATION

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air): UN1263; PAINT RELATED MATERIAL; CLASS 3; PG III

SECTION 15. REGULATORY INFORMATION

Product Identifier: Polyurea Crack Filler - B



SECTION 16. OTHER INFORMATION			
Date of Preparation	January 4, 2023		
Date of Last Revision	January 4, 2023		
Revision Indicators			
References			

<u>Notice:</u> The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that American Resins will not be liable for any damages resulting from its use since American Resins cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.

Product Identifier: Polyurea Crack Filler - B Page 8 of 8