



3KR0
SSLWHFKL0FRP

CLEAN-UP:

Use ketones or xylene for clean-up.

PRODUCT LIMITATIONS:

- ‡ Paint to be applied at supplied VOC without reduction.
- ‡ This ratio has been set for optimal performance of the product.
- ‡ Equipment application guidelines are only guidelines and application/process parameters will dictate exact requirements.

obtain the most recent Product Data Sheet for the product being used. The information, rating, and opinions stated here pertain to material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling, methods of application, which are not known or under our control, PPI cannot make any warranties as to the end result.

Cautions

DANGER! Contents are **FLAMMABLE**.

Vapors may cause flash fires. Keep away from heat, sparks and open flame. During use, and until all vapors are gone, keep well ventilated. Do not smoke. Extinguish all flames, pilot lights and heaters. Turn off stoves, electric tools, appliances, and any other source of ignition.

Catalyst CONTAINS ISOCYANATES. People who have chronic (long term) lung or breathing problems or have had a reaction to isocyanates, must not be in the area where this product is being applied where overspray is present, a positive pressure air-supplied respirator should be worn. If unavailable, a properly fitted organic vapor/particulate respirator may be effective. Consult catalyst SDS for further information.

VAPOR HARMFUL IF INHALED CAUSING DIZZYNESS, HEADACHE OR NAUSEA, IRRITATES EYES, SKIN AND RESPIRATORY TRACT. Use a properly fitted Organic vapor Respirator. Follow respirator PPE requirements. Do not inhale vapors. Avoid contact with eyes. Keep container closed when not in use. Do not transfer contents to other containers for storage. Before use please consult the Safety Data Sheet for further precautions.

FIRST AID:

- If inhaled:** If affected, remove from exposure. Restore breathing. Keep warm and quit.
- If on skin:** Wash affected area thoroughly with soap and water. Remove all contaminated clothing/laundry before reuse.
- If swallowed:** Get medical attention immediately.

Spill and Waste: Ventilate and remove with inert absorbent. Incinerate in approved facility. Do not incinerate in closed containers. Dispose of in accordance with federal, state, and local regulation regarding pollution.

Delayed effects from long term overexposure:

Contains solvents, which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

FOR INDUSTRIAL USE ONLY

Note: Product data sheets are periodically updated to reflect new information relating to the product. It is important that the customer

